



ADRD241OS



31.88" x 23.38" x 22.5" (H x W x D)

24 in. wide ADA compliant 2-drawer outdoor all-refrigerator for residential or commercial use, with panel-ready stainless steel drawer fronts, black cabinet, and digital controls

Highlights:

Weatherproof construction for safe use in the outdoors

32" height for use under lower ADA compliant counters

Panel-ready drawers allow you to customize the look to match existing cabinetry

Product Features:

2-Drawer All-Refrigerator	24" wide 3.7 cu.ft. all-refrigerator with two gliding drawers
Weatherproof design for outdoor use	Durable construction allows safe installation in outdoor kitchens
ADA compliant design	Sized just under 32" high to allow installation under lower ADA compliant counters
Built-in capable	Front-breathing design allows you to make the best use of space by installing your appliance under the counter and flush with other cabinets in 24" wide openings
Stainless steel drawers	Drawer interiors and exteriors are fully constructed from 304 grade stainless steel for weatherproof durability and elegant style
Panel-ready drawer fronts	Drawers accept overlay panels (size: 23.43" x 14.1" at 3/4" thick) to let you seamlessly blend the refrigerator into cabinetry design
Professional handles	Sleek stainless steel handles add an elegant touch to any setting
Frost-free	No-frost operation for minimum user maintenance
Digital thermostat	Electronic controls located on the top drawer ensure intuitive temperature management, with an external readout that can switch from Celsius to Fahrenheit at the touch of a button



Sound Level 33 dB

Interior Height 1	8.0" (20 cm)
Interior Width 1	17.0" (43 cm)
Interior Depth 1	14.5" (37 cm)
Interior Height 2	8.0" (20 cm)
Interior Width 2	17.0" (43 cm)
Interior Depth 2	14.5" (37 cm)

Compressor Step Height	4.0" (10 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	3.5" (9 cm)



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL 718-893-3900 FAX 844-478-8799**

